

Flotation Tanks


MetaLine® Series 700 – Corrosion & wear protection in mineral processing plants



MetaLine meets heavy duty off-shore corrosion protection standards. Electro-chemical anodic properties combined with a rubberlike atmospheric encapsulation surpasses over 6,000 hours saltspray-chamber test as per ASTM. Withstands up to 70 bar (1,000 psi) of water pressure.

Applications

- flotation cells
- flotation tanks
- flotation accessories
- attritor mills (wet milling)



Reference

- many times more erosion resistant than steel or natural rubber
- partially quickly and easily repairable or recoatable
- good chemical resistance from pH 3 to 11 at standard temperature



MetaLine Surface Protection GmbH | DE-71157 Hildrizhausen (Germany) | Robert-Bosch-Str. 5-11
Tel. +49 (0)7034 3100-0 | Fax +49 (0)7034 3100-5 | www.metaline.com | info@metaline.de

Subject to technical modifications! Information and application examples in this document are provided to the best of our knowledge. However, they also apply without guarantee in reference to the exclusive rights of third parties and do not release the user to check the products and processes for their suitability and material tolerance regarding their intended use. We do not assume liability for the application results. Copyright by MetaLine Surface Protection GmbH, DE-71157 Hildrizhausen (1960 - 2023). MetaLine is a registered trademark of our company.