

Drive Pulleys / Rollers

MetaLine® Series 700 – Elastomeric coatings for friction improvement



Sprayable elastomeric compounds for the repair of existing linings or complete new roller coatings. Available hardnesses 60 / 85 / 95 Shore A in a seamless quality. End-faces can be covered as well.

Applications

- drive rollers
- vacuum rollers
- transport rollers
- pulley lagging
- friction wheels
- diabolo rollers
- cable reels



Reference

- mechanically precise remachining up to 1/100 mm (1/2 mil)
- static friction values up to $\mu(0) = 0.7$ ensure maximum conveying effect
- under certain circumstances directly deployable without mechanical post-processing



MetaLine Surface Protection GmbH | DE-71157 Hildrizhausen (Germany) | Robert-Bosch-Str. 5-11
Tel. +49 (0)7034 3100-0 | Fax +49 (0)7034 3100-5 | www.metaline.com | info@metaline.de

Subject to technical modifications! Information and application examples in this document are provided to the best of our knowledge. However, they also apply without guarantee in reference to the exclusive rights of third parties and do not release the user to check the products and processes for their suitability and material tolerance regarding their intended use. We do not assume liability for the application results. Copyright by MetaLine Surface Protection GmbH, DE-71157 Hildrizhausen (1960 - 2023). MetaLine is a registered trademark of our company.