

Slurry Pipes

MetaLine® Series 700 – **Service life extension when transporting highly abrasive liquids**



Designed for the most abrasive media. Can be applied in any desired layer thickness depending on the load. Proper chemical resistance. Also suitable to improve flange sealing situations.

Applications

- pipes / pipelines
- connectors
- pipe bends / elbows
- manifolds

Maximum coating length for straight pipes (ML 760)

Diameter: minimum 4 inch	max. length	6,5 ft
Diameter: 4 - 12 inch	max. length	10 ft
Diameter: 12 - 30 inch	max. length	13 ft
Diameter: plus 30 inch	max. length	20 ft



Reference

- useful up to a grain size of 8 mm (315 mils) and smaller
- also as a repair method for already existing damaged rubber linings
- designed for single part coatings at the construction site



MetaLine Surface Protection GmbH | DE-71157 Hildrizhausen (Germany) | Robert-Bosch-Str. 5-11
Tel. +49 (0)7034 3100-0 | Fax +49 (0)7034 3100-5 | www.metaline.com | info@metaline.de

Subject to technical modifications! Information and application examples in this document are provided to the best of our knowledge. However, they also apply without guarantee in reference to the exclusive rights of third parties and do not release the user to check the products and processes for their suitability and material tolerance regarding their intended use. We do not assume liability for the application results. Copyright by MetaLine Surface Protection GmbH, DE-71157 Hildrizhausen (1960 - 2023). MetaLine is a registered trademark of our company.